Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



AX104615 Faceplates and Panels - KeyConnect Multi-User Adapter 12-Port



For more Information please call

1-800-Belden1



General Description:

KeyConnect Multi-User Outlet Adapter 12-Ports

Sox to accept KeyConnect modules that are suitable for use with Belden 30, 2400 and 1200.

Related Parts: - Compatible with 10GX, CAT6+ and CAT5E KeyConnect Modular Jacks and Multimedia Modules

Physical Characteristics (Connectivity)

Capacity

Max. Capacity: 12 KeyConnect Modules

Access

Front Connection: Flush

Dimensions

Dimensions:

Height (mm) Width (mm) 43.942 228.092

Materials

Materials:

Description Material

Multi Media KeyConnect Adapter | Metal

Color

Color: Black

Weight

Weight: 0.176 kg

Packaging

 Packaging:
 Individually packaged in a plastic bag

Mechanical Characteristics (Connectivity)

Footprint/Type: KeyConnect

Storage Temperature Range: -40°C To +70°C

Installation Temperature Range: -10°C To +60°C

Operating Temperature Range: -10°C To +60°C

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

 EU Directive 2002/95/EC (RoHS):
 Yes

 EU RoHS Compliance Date (mm/dd/yyyy):
 07/01/2006

 MII Order #39 (China RoHS):
 Yes

Suitability

Suitability - Indoor: Yes

Transmission Characteristics (Connectivity)

Notes (Overall)

Notes: For proper installation refer to the installation guide included with the product or visit our web site at http://www.belden.com

Product Family

Part Numbers:

Description	Belden Part Number
MDVO Adapter Strip, 12-port, Empty, Black	AX100223
CAT5E HD-BIX Connector Module Strip, Universal Wiring 12-port. T568A/B	AX100224

Page 1 of 2 03-13-2017

Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



AX104615 Faceplates and Panels - KeyConnect Multi-User Adapter 12-Port

CAT5E HD-110 Connector Module Strip, Universal Wiring 12-port, T568B/	A AX100494
KeyConnect Adapter Strip, 12-port, Empty, black	AX104615

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX104615	1 EA	0.389 LB			KEYCONNECT ADAPTER STRIP,

Revision Date: 11-11-2011 Revision Number: 0

© 2017 Belden, Inc All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/5FC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Page 2 of 2