

$V_{CES} = 1200V$

$I_C = 200A$  at  $T_C = 80^\circ C$


$V_{CE(ON)} = 1.70V$  at  $I_C = 200A$

**IGBT Half-Bridge  
POWIR 62™ Package**



**Applications:**

- Industrial Motor Drive
- Uninterruptible Power Supply
- Welding and Cutting Machine
- Switched Mode Power Supply
- Induction Heating



Features	Benefits
Low $V_{CE(ON)}$ and Switching Losses	High Efficiency in a Wide Range of Applications
100% RBSOA Tested	Rugged Transient Performance
<b>POWIR 62™</b> Package	Industry Standard
Lead Free	RoHS Compliant, Environmental Friendly

Base Part Number	Package Type	Standard Pack	Quantity	Orderable Part Number
IRG7U200HF12B	<b>POWIR 62™</b>	Box	45	IRG7U200HF12B

**Absolute Maximum Ratings of IGBT**

$V_{CES}$	Collector to Emitter Voltage	1200	V
$V_{GES}$	Continuous Gate to Emitter Voltage	±20	V
$I_C$	Continuous Collector Current	$T_C = 80^\circ C$	200 A
		$T_C = 25^\circ C$	400 A
$I_{CM}$	Pulse Collector Current	$T_J = 175^\circ C$	400 A
$P_D$	Maximum Power Dissipation (IGBT)	$T_C = 25^\circ C, T_J = 175^\circ C$	1130 W
$T_J$	Maximum IGBT Junction Temperature	175	°C
$T_{JOP}$	Maximum Operating Junction Temperature Range	-40 to +150	°C
$T_{stg}$	Storage Temperature	-40 to +125	°C

**Electrical Characteristics of IGBT at  $T_J = 25^\circ\text{C}$  (Unless Otherwise Specified)**

Parameter		Min.	Typ.	Max.	Unit	Test Conditions	
$V_{(BR)CES}$	Collector to Emitter Breakdown Voltage	1200			V	$V_{GE} = 0V, I_C = 2mA$	
$V_{GE(th)}$	Gate Threshold Voltage	3.4	4.2	4.9	V	$I_C = 10mA, V_{CE} = V_{GE}$	
$V_{CE(ON)}$	Collector to Emitter Saturation Voltage		1.70	2.00	V	$T_J = 25^\circ\text{C}$	$I_C = 200A, V_{GE} = 15V$
			1.90		V	$T_J = 125^\circ\text{C}$	
$I_{CES}$	Collector to Emitter Leakage Current			2	mA	$V_{GE} = 0V, V_{CE} = V_{CES}$	
$I_{GES}$	Gate to Emitter Leakage Current			400	nA	$V_{GE} = \pm 20V, V_{CE} = 0V$	
$R_{Gint}$	Internal Gate Resistance		1.25		$\Omega$		

**Switching Characteristics of IGBT**

Parameter		Min.	Typ.	Max.	Unit	Test Conditions	
$t_{d(on)}$	Turn-on Delay Time		1100		ns	$T_J = 25^\circ\text{C}$	$V_{CC}=600V, I_C = 200A, R_G = 15\Omega, V_{GE}=\pm 15V, \text{Inductive Load}$
			1080			$T_J = 125^\circ\text{C}$	
$t_r$	Rise Time		200		ns	$T_J = 25^\circ\text{C}$	
			205			$T_J = 125^\circ\text{C}$	
$t_{d(off)}$	Turn-off Delay Time		900		ns	$T_J = 25^\circ\text{C}$	
			950			$T_J = 125^\circ\text{C}$	
$t_f$	Fall Time		110		ns	$T_J = 25^\circ\text{C}$	
			140			$T_J = 125^\circ\text{C}$	
$E_{on}$	Turn-on Switching Loss		19.0		mJ	$T_J = 25^\circ\text{C}$	
			22.9			$T_J = 125^\circ\text{C}$	
$E_{off}$	Turn-off Switching Loss		15.2		mJ	$T_J = 25^\circ\text{C}$	
			19.8			$T_J = 125^\circ\text{C}$	
$Q_g$	Total Gate Charge		2100		nC	$T_J = 25^\circ\text{C}$	
$C_{ies}$	Input Capacitance		20.0		nF	$V_{CE} = 25V, V_{GE} = 0V, f = 1MHz, T_J = 25^\circ\text{C}$	
$C_{oes}$	Output Capacitance		1.08				
$C_{res}$	Reverse Transfer Capacitance		0.75				
RBSOA	Reverse Bias Safe Operating Area	Trapezoid				$I_C = 400A, V_{CC} = 960V, V_P = 1200V, R_G = 15\Omega, V_{GE} = +15V \text{ to } 0V, T_J = 150^\circ\text{C}$	

**Absolute Maximum Ratings of Freewheeling Diode**


$V_{RRM}$	Repetitive Peak Reverse Voltage	1200	V
$I_F$	Diode Continuous Forward Current, $T_C = 25^\circ\text{C}$	400	A
	Diode Continuous Forward Current, $T_C = 80^\circ\text{C}$	200	
$I_{FM}$	Pulse Diode Current	400	A

**Electrical and Switching Characteristics of Freewheeling Diode**


Parameter		Typ.	Max.	Unit	Test Conditions	
$V_F$	Forward Voltage	2.00	2.70	V	$T_J = 25^\circ\text{C}$	$I_F = 200\text{A}$ , $V_{GE} = 0\text{V}$
		2.20			$T_J = 125^\circ\text{C}$	
$I_{rr}$	Peak Reverse Recovery Current	65		A	$T_J = 25^\circ\text{C}$	$I_F = 200\text{A}$ , $di/dt = 960\text{A}/\mu\text{s}$ , $V_{rr} = 600\text{V}$ , $V_{GE} = -15\text{V}$
		105			$T_J = 125^\circ\text{C}$	
$Q_{rr}$	Reverse Recovery Charge	9.65		$\mu\text{C}$	$T_J = 25^\circ\text{C}$	
		21.80			$T_J = 125^\circ\text{C}$	
$E_{rec}$	Reverse Recovery Energy	3.20		mJ	$T_J = 25^\circ\text{C}$	
		8.40			$T_J = 125^\circ\text{C}$	

**Module Characteristics**


Parameter		Min.	Typ.	Max.	Unit
$V_{iso}$	Isolation Voltage (All Terminals Shorted), $f = 50\text{Hz}$ , 1minute			2500	V
$R_{\theta JC}$	Junction-to-Case (IGBT)		0.132		$^\circ\text{C}/\text{W}$
$R_{\theta JC}$	Junction-to-Case (Diode)		0.204		$^\circ\text{C}/\text{W}$
$R_{\theta CS}$	Case-To-Sink (Conductive Grease Applied)		0.1		$^\circ\text{C}/\text{W}$
M	Power Terminals Screw: M6	3.0		5.0	N·m
M	Mounting Screw: M6	4.0		6.0	N·m
G	Weight		230		g




**Fig.1 Typical IGBT Saturation Characteristics**




**Fig.2 Typical IGBT Output Characteristics**




**Fig.3 Typical Freewheeling Diode Characteristics**




**Fig. 4 Typical Capacitance Characteristics**




**Fig.5 Typical Switching Loss vs. Collector Current**




**Fig.6 Typical Switching Loss vs. Gate Resistance**




**Fig.7 Typical Load Current vs. Frequency**



**Fig.8 Reverse Bias Safe Operation Area (RBSOA)**




**Fig.9 Typical Transient Thermal Impedance (IGBT)**




**Fig.10 Typical Transient Thermal Impedance (Diode)**

**Internal Circuit:**



**Package Outline (Unit: mm):**



**Qualification Information<sup>†</sup>**

Qualification Level	Industrial
Moisture Sensitivity Level	Not Applicable
RoHS Compliant	Yes

† Qualification standards can be found at International Rectifier’s web site: <http://www.irf.com/product-info/reliability/>